



# M.D. STETSON

## ADHERE UNDERCOAT

A water-based sealer and undercoat that improves floor finish adhesion, appearance and durability when used on worn and porous floors. Resists removal with routine strippers so that finish can be removed and reapplied without damage to the sealer. Reduces number of coats of finish necessary for high speed buffing. Use on all composition resilient flooring, asphalt, concrete and terrazzo.

### DIRECTIONS FOR USE

**Note: Adhere Undercoat** cannot be used alone. An application of floor finish must be used after sealer is dry.

1. Strip floor completely of old finish with a Stetson stripper, such as **60 Seconds Stripper**. Rinse floor clean of all residue. Rinse with Winterclean.
2. Apply **Adhere Undercoat** with medium even coats using a finish mop or finish applicator.
3. Porous floors may require 2 coats. Apply second coat after first is completely dry.
4. Always apply a Stetson finish over sealer.

**Drying time:** 20-30 minutes per coat. Provide ventilation.

**Coverage:** Between 2000-3000 sq. ft. per gallon.

### SPECIFICATIONS

Appearance .....milky white liquid  
 Fragrance ..... slight acrylic odor  
 pH..... 8.2-8.6  
 Specific gravity..... 1.02-1.04  
 Storage stability .....1 year

**Refer to the safety data sheet (SDS) for detailed safety, health and environmental information.**

### PACKAGING

Available in 1 gallon plastic containers.

June 2017