



M.D. STETSON

ALLKLEEN STETCOSOLVE

Stetcosolve is a fast-acting, highly concentrated cleaner/degreaser. Stetcosolve dissolves soil from hard to clean surfaces and is recommended for use as a remover of hardened layers and deposits of animal fat, grease, protein substances, carbon, embedded soil and food stuff. Stetcosolve may be used to clean machinery, concrete floors, air filters, locker room and pool floors, semi-trailers, counter-tops, supermarket storage and warehouse areas. Stetcosolve is rust inhibited for metal cleaning but should not be used on polished aluminum, magnesium or finished surfaces.

DIRECTIONS FOR USE:

NOTE: Always use Stetcosolve diluted with water. If concentrate is spilled on floor surface wipe up immediately. Stetcosolve is rust inhibited for metal cleaning however should not be used on polished aluminum, magnesium, painted or varnished surfaces. If unsure of surface, test a small unseen area.

1. For all purpose spray and wipe cleaning, use 2-4 oz. Stetcosolve per gal. of water. Spray on surface, let dwell and wipe clean with a cloth or paper towel. Rinse surface with clear water.
2. For degreasing, removal of carbon deposits, and heavy soil, including kitchen ranges and exhaust hoods, use 8 oz. Stetcosolve per gal. of water. Allow solution to dwell, then remove loosened soil with a scraper, steel wool or scrub pad. Rinse surface with clear water.
3. For pressure washer, use 4-8 oz. Stetcosolve per gal. of water. Apply with low pressure onto surface, let dwell, and rinse with high pressure mode.
4. For damp mopping light soil or in automatic scrubbing machines, use 1 oz. Stetcosolve per gal. of cold water. No rinse is required. Do not use on floors coated with floor finish.
5. For damp mopping heavy soil, or in automatic scrubbers, use 2 oz. Stetcosolve per gal. of cold water. No rinse required. Do not use on floors coated with floor finish.
6. For routine mopping of kitchen floors, use 1 - 2 oz. Stetcosolve per gal. of water. Change mop water frequently as it becomes soiled.
7. For deep cleaning and degreasing of grouted floors, including kitchens and restrooms, use 4-8 oz. Stetcosolve per gal. of water. Apply with autoscrubber, mop or applicator. Double scrub area with autoscrubber or floor machine and then pick up the cleaning solution from surface with an autoscrubber, clean mop or wet-vacuum pick-up.

SPECIFICATIONS:

Color	violet
Odor.....	pine
Glycol ether content	8%
pH	12 - 13
Weight per gallon	8.37 lbs.
Non-volatile matter	5% ± 0.2%

CAUTION: May cause burns. Eye irritant. Avoid contact with eyes, mucus membranes and excessive prolonged contact with skin. In case of such contact, wash thoroughly with water. If irritation persists, get medical attention. The use of safety gloves and glasses is required. Read MSDS before use. For use only by trained professional cleaning personnel.

FIRST AID: If taken internally drink large amounts of citrus juice. Call a physician immediately. In case of contact with skin and eyes, flush with water for 15 minutes. For eyes get immediate medical attention

Refer to the material safety data sheet (MSDS) for detailed safety, health and environmental information.

PACKAGING:

Available in 1 gallon jugs, 5 gallon pails, 30 and 55 gallon drums.

December 2012