

M.D. STETSON



ARMORGUARD FLOOR FINISH

This urethane-fortified thermoplastic finish of the highest quality is specially designed for use in heavy traffic areas that are not maintained on a regular basis. Armorguard dries to a hard, non-powdering, scuff resistant, super high gloss and crystal-clear finish. Armorguard is easy to-apply and maintain and will give exceptional protection, slip-resistance, and a brilliant shine. Armorguard produces a thermoplastic film that responds to buffing at any RPM when using a Stetson maintainer or restorer. A floor maintenance program encompassing a routine buffing operation will improve scuff, black-heel marking, and slip-resistance and extend the life of the finish while giving a brilliant gloss.

DIRECTIONS FOR USE:

1. **Preparation:** Strip or scrub floor removing the desired amount of finish using a Stetson stripper or Winterclean for scrubbing. Thoroughly rinse the floor using Winterclean. Application of Armorguard should be on completely clean floor.

Please refer to Stetson's "Catch the Training" Strip & Refinish or Scrub & Recoat training guides for detailed instructions.

2. **Optional:** If surface is in worn condition or porous, use Armorguard or a Stetson sealer first to seal the floor.
3. **Application:** Do not dilute Armorguard. Apply with a clean finish mop, microfiber pad or applicator, spreading evenly. Apply medium coats. If finish is to be maintained with a high speed buffing program, a base film of 4 to 6 coats of finish is recommended. Allow each coat to dry before applying the next coat. Application should not exceed more than 4 coats of finish in one day. Dry time will range from 20-45 minutes per coat depending on atmospheric conditions. On highly humid days extend dry times and reduce the number of coats applied per day.
 - Always wait 24 hours before buffing newly applied finish.
 - Never use a stripper or a high pH cleaner for routine maintenance.

COVERAGE:

1500-3000 square feet, depending on the method of application and the porosity of the floor.

PACKAGING:

Available in 1 gallon jugs, 5 gallon plastic pails, 30 and 55 gallon drums.

Refer to the material safety data sheet (MSDS) for detailed safety, health and environmental information.

MAINTENANCE:

1. Sweep or dry mop floors on a daily basis.
2. Damp mop or autoscrub with a Stetson neutral floor cleaner or a germicidal cleaner daily. Substitute Winterclean in the winter to remove de-icing salt residues.
3. If a high speed buffing program is used, damp mop or autoscrub with one of Stetson's premium finish restorers prior to buffing. The result will be a sensational "wet look" gloss, increased slip-resistance, and an extended life for the finish.
4. Worn or soiled areas can be recoated with 1 or 2 coats of Armorguard as needed. Prior to application, scrub the floor with Winterclean using an autoscrubber or floor machine and the appropriate floor machine pad.

Please refer to Stetson's "Catch the Training" Daily Floorcare or Scrub & Recoat training guides for detailed instructions.

SPECIFICATIONS:

Appearance.....	white emulsion
Solids.....	21% + 0.2
Pounds per gallon.....	8.60 + .05
Viscosity (Brookfield).....	2.65 + 0.15 cps
Gloss.....	excellent
Levelling	excellent
Crazing	none
Hazing.....	none
Water spot resistance	
1 hour.....	very good
24 hours	excellent



Floor coating and finishing materials as to slip resistance only. 3NRJ