



M.D. STETSON

FIRST IMPRESSION FLOOR FINISH

This thermoplastic polymer blend of the highest quality is specially designed for use in heavy traffic areas that are not maintained on a regular basis, such as classrooms. **First Impression** dries to a hard, non-powdering, scuff resistant, super high gloss and crystal-clear finish. **First Impression** is easy to apply and maintain and will give exceptional protection, slip-resistance, and a brilliant shine. **First Impression** produces a thermoplastic film that responds to buffing at any RPM when using a Stetson maintainer or restorer. A floor maintenance program encompassing a routine buffing operation will improve resistance to scuffs, black-heel marks, and slips, while extending the life of the finish.

DIRECTIONS FOR USE:

1. Completely strip old finish from surface with any of M.D. Stetson's quality strip-pers.
2. An option: If surface is in worn condition or porous, use **Adhere Undercoat** as a sealer.
3. The finish: Apply finish with a clean finish mop or applicator, spreading evenly. Apply medium coats. If finish is to be maintained with a high speed buffing program, a base film of 4 to 6 coats of finish is recommended. Allow each coat to dry before applying next coat. Application should not exceed more than 4 coats of finish in one day.

Note: Never use a stripper for routine cleaning.

Drying time: 20-35 minutes per coat.

Coverage: 1500 to 3000 square feet, depending on application method and the porosity of floor.

Refer to the material safety data sheet (MSDS) for detailed safety, health and environmental information.

PACKAGING:

Available in 1 gallon jugs, 5 gallon plastic pails, 30 and 55 gallon drums.

MAINTENANCE:

1. Floor should be swept or dry mopped on a daily basis.
2. **First Impression** can be maintained daily by damp mopping or autoscrubbing with one of Stetson's neutral cleaners or germicidal cleaners. Substitute **Winterclean** in the winter to remove de-icing salt residues.
3. If a high speed buffing program is used: damp mop or autoscrub with one of Stetson's premium finish restorers; **Enhancer** or **Tone Up**. The buffed result will be a sensational "wet look" gloss, increased slip-resistance, and an extended life for the finish.

Please refer to Stetson's "Catch the Training" Strip & Refinish, Daily Floorcare or Scrub & Re-coat training guides for detailed instructions.

SPECIFICATIONS:

Appearance	white emulsion
Pounds per Gallon	8.5 ± 0.05
Viscosity (Brookfield).....	1.4 ± 0.15 cps
Gloss	Excellent
Leveling.....	Excellent
Crazing.....	None
Hazing.....	None
Recoatibility.....	Excellent
Wet Abrasion.....	Excellent

May 2014