



M.D. STETSON

NIGHTOWL FLOOR FINISH

A state of the art, high-solids, thermoplastic polymer-blend that produces a finish responsive to high speed buffing, including propane machines. **Nightowl Floor Finish** dries to a hard clear film, highly resistant to scuffing and black heel marking; is easy to-apply and maintain; and offers exceptional protection, slip-resistance, and a brilliant shine. **Nightowl Floor Finish** responds to buffing at any RPM when using a Stetson maintainer or restorer. A floor maintenance program encompassing a routine buffing operation will improve resistance to scuffs, black-heel marks, and slips, while extending the life of the finish. Available in 18%, 20% and 25% solids.

DIRECTIONS FOR USE:

Preparation: Strip or scrub floor removing the desired amount of finish using a Stetson stripper or Winterclean for scrubbing. Thoroughly rinse the floor using Winterclean. Application of **Nightowl Floor Finish** should be on completely clean floor.

Optional Step: If surface is in worn condition or porous, use **Nightowl Floor Finish** or a Stetson sealer first to seal the floor.

Application: Do not dilute **Nightowl Floor Finish**. Apply with a clean finish mop, microfiber pad or applicator, spreading evenly. Apply medium coats. If finish is to be maintained with a high speed buffing program, a base film of 4 to 6 coats of finish is recommended. Allow each coat to dry before applying the next coat. Application should not exceed more than 4 coats of finish in one day. Dry time will range from 20-45 minutes per coat depending on atmospheric conditions. On highly humid days extend dry times and reduce the number of coats applied per day.

- Always wait 24 hours before buffing newly applied finish.
- Never use a stripper or a high pH cleaner for routine maintenance.

COVERAGE:

1500-3000 square feet, depending on the method of application and the porosity of the floor.

Please refer to Stetson's "Catch the Training" Strip & Refinish, Daily Floorcare or Scrub & Re-coat training guides for detailed instructions.

PACKAGING:

Available in 1 gallon jugs, 5 gallon plastic pails, and 55 gallon drums.

Maintenance:

- Sweep or dry mop floors on a daily basis.
- Damp mop or autoscrub with a Stetson neutral floor cleaner or a germicidal cleaner daily. Substitute Winterclean in the winter to remove de-icing salt residues.
- If a high speed buffing program is used, damp mop or autoscrub with one of Stetson's premium finish restorers prior to buffing. The result will be a sensational "wet look" gloss, increased slip-resistance, and an extended life for the finish.
- Worn or soiled areas can be recoated with 1 or 2 coats of **Nightowl Floor Finish** as needed. Prior to application, scrub the floor with Winterclean using an autoscrubber or floor machine and the appropriate floor machine pad.

SPECIFICATIONS:

Appearance	White emulsion
pH.....	0.0
Pounds per gallon	8.60 + .05
Gloss	Excellent
Levelling	Excellent
Crazing	None
Hazing.....	None
Water spot resistance	
1 hour	Very good
24 hours	Excellent

Refer to the safety data sheet (SDS) for detailed safety, health and environmental information.



Floor coating and finishing materials as to slip resistance only.
3NRJ

April 2013



11 Norfolk Street • Mansfield, MA 02048
877-4-JANSAN • www.nextgensupply.com

