# M.D. STETSON

### **SPRAZOL**

A highly concentrated, all purpose cleaner that can be used for multitude of applications. Use at lower dilutions for routine cleaning and at higher dilutions for heavy duty cleaning and degreasing. Sprazol will not leave streaks on hard surfaces. Removes grease, dirt, black-heel and scuff marks, crayon, pencil, mold, and soot. Sprazol contains corrosion inhibitors for use on metals, such as engines and other machinery.

Sprazol is safe for most surfaces. However, do not to use for routine cleaning on floors with an acrylic or acrylic/urethane finish at over 1 oz. per gallon dilution. Floors coated with an oil-modified urethane will not be harmed. Also do not use strong dilutions on polished aluminum, magnesium, painted and varnished surfaces. Biodegradeable, low-sudsing and pleasantly scented.

#### **DIRECTIONS FOR USE:**

M.D. STETSON

- 1. For all purpose spray and wipe cleaning, use 2 ounces Sprazol per gallon of water. Spray on surface, let dwell and wipe clean with a cloth or paper towel. No rinse is necessary.
- 2. For heavy duty spray and wipe cleaning and degreasing, use 3 8 ounces Sprazol per gallon of water. Spray on surface, let dwell and wipe clean with a cloth or paper towel. No rinse is necessary.
- 3. For use with a pressure washer, use 3 8 ounces Sprazol per gallon of water. Apply with low pressure onto surface, let dwell, and rinse with high pressure mode.
- 4. For damp mopping light soil or in automatic scrubbing machines, use 1/2 -1 ounces Sprazol per gallon of cold water. No rinse is required. Not recommended for daily cleaning of floors finished with floor finish.
- 5. For damp mopping heavy soil, or in automatic scrubbers, use 2 ounces Sprazol per gallon of cold water. No rinse required
- 6. For routine mopping of kitchen floors, use 2 ounces Sprazol per gallon of water. Change mop water frequently as it becomes soiled.
- 7. For deep restorative cleaning and degreasing of grouted floors including kitchens and restrooms, use 4-8 ounces Sprazol per gallon of water. Apply the solution with an autoscrubber, mop or applicator, double scrub the area with the autoscrubber or floor machine and then pick up the cleaning solution from surface with an autoscrubber, clean mop or wet-vacuum pick-up.
- 8. For deep scrubbing floors finished with floor finishes with an autoscrubber, use 2 ounces Sprazol per gallon of cold water. Apply the solution without the vacuum system and the squeegee in the up position. Double scrub the area and then vacuum up the solution. Final rinse with Winterclean before applying floor finish.

Continued next column

9. For deep scrubbing floors finished with floor finishes with manual equipment, use 2 ounces Sprazol per gallon of cold water. Apply the solution with a mop or applicator. Double scrub the area with a floor machine and then pick up the cleaning solution from surface with clean mop or wet-vacuum. Final rinse with Winterclean before applying floor finish.

NOTE: This product will remove floor finish. Do not use full strength. If spilled, wipe up immediately

**Caution:** Rubber gloves should be worn when using this product. Do not use strong solutions of Sprazol on polished aluminum, magnesium, painted and varnished surfaces. If concentrate is spilled on floor surface wipe up immediately with damp mop.

#### **SPECIFICATIONS:**

| Color            | pale yellow            |
|------------------|------------------------|
| Odor             | pine                   |
| Content          | 20% active ingredients |
| рН               |                        |
| Specific gravity |                        |

**WARNING:** Keep out of reach of children. Can cause eye or skin burns. Avoid contact with eyes, skin and clothing. Harmful if swallowed. Keep container closed when not in use. Do not mix with ammonia, bleach or other cleaning products. This product contains potassium hydroxide and monoethanolamine. Do not use strong dilutions of this product on aluminum, magnesium, painted or varnished surfaces. If concentrate is spilled wipe immediately with damp mop. Do not use full strength.

## Refer to the material safety data sheet (MSDS) for detailed safety, health and environmental information.

#### PACKAGING:

Available in 1 gallon jugs, 5 gallon pails, 30 and 55 gallon drums.

92 York Avenue • Randolph, MA 02368 • www.mdstetson.com TEL: 781-986-6161 • 800-255-8651 • FAX: 781-961-1764

January 2013

