



PRODUCT DATA SHEET

AQUATHANE Concrete and Stone Water-Based Sealer and Finish

Aquathane is a water-based blend of acrylic and urethane polymers, utilizing the most recent developments in sealer technology. Will not discolor or yellow over time. Specially formulated for use on concrete, quarry tile, slate, and other masonry surfaces. Easy-to-apply, non-flammable, minimal odor. Application tools are readily cleaned with water.

DIRECTIONS FOR USE

On a properly prepared floor:

- Apply full strength in even, medium coats
- Apply 4-6 base coats, adding coats as needed
- Drying time: approximately 1 hour per coat minimum, depending on humidity
- Coverage: 500-2500 sq.ft. per gallon.

Note: Aquathane should not be applied to new concrete surfaces until the concrete has cured for at least seven days.

Please refer to Stetson's "Catch the Training" Strip & Refinish, Daily Floorcare or Scrub & Recoat training guides for detailed instructions.



SPECIFICATIONS:

Appearance	Milky white liquid
Fragrance added	None
pH	8.2-8.6
Specific gravity	1.02-1.04
Viscosity (Brookfield)	<100 cps
Gloss	Excellent
Leveling	Excellent
Crazing	None
Hazing	None
Recoatibility	Excellent

Refer to the Safety Data Sheet (SDS) for detailed safety, health and environmental information.

PACKAGING:

Available in 1-gallon containers, 5-gallon pails., and 55-gallon drums.

August 2023



**11 Norfolk Street
Mansfield, MA 02048
877-4-JANSAN
www.nextgensupply.com**

Next-Gen Supply Group is part of Envoy Solutions company, a specialized distributor and solution provider in jan-san, foodservice, packaging, and marketing execution.